

**IN THE CLAIMS:**

Please amend the claims as follows:

1. (Cancelled)
2. (Cancelled)
3. (Cancelled)
4. (Cancelled)
5. (Cancelled)
6. (Cancelled)
7. (Cancelled)
8. **(Currently Amended)** A method, comprising:  
receiving a pair of input clock signals;  
utilizing a stratum clock state machine to control a multiplexer;  
utilizing the multiplexer to switch an input of a main clock between each of the pair of  
input clock signals;  
inducing a phase build-out activity;  
transmitting an output clock signal;  
utilizing the stratum clock state machine to set the main clock to a main clock holdover  
state; and ~~The method of claim 6, further comprising~~  
applying a frequency history to a frequency synthesizer in the main clock.
9. **(Original)** The method of claim 8, wherein applying the frequency history includes applying an approximately twenty-five second frequency history.

10. **(Original)** The method of claim 8, further comprising forcing a phase measurement circuit into a zero phase error state by preloading a phase measurement counter with a zero substantially on an edge of an input signal.

11. **(Currently Amended)** A method, comprising:  
receiving a pair of input clock signals;  
utilizing a stratum clock state machine to control a multiplexer;  
utilizing the multiplexer to switch an input of a main clock between each of the pair of  
input clock signals;  
inducing a phase build-out activity;  
transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
utilizing the stratum clock state machine to select a short time constant filter in the main clock.

12. **(Currently Amended)** A method, comprising:  
receiving a pair of input clock signals;  
utilizing a stratum clock state machine to control a multiplexer;  
utilizing the multiplexer to switch an input of a main clock between each of the pair of  
input clock signals;  
inducing a phase build-out activity;  
transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
utilizing the stratum clock state machine to select a long time constant filter in the main clock.

13. **(Currently Amended)** A method, comprising:  
receiving a pair of input clock signals;  
utilizing a stratum clock state machine to control a multiplexer;  
utilizing the multiplexer to switch an input of a main clock between each of the pair of

input clock signals;

inducing a phase build-out activity;

transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
utilizing the stratum clock state machine to select a programmable filter.

14. **(Currently Amended)** A method, comprising:

receiving a pair of input clock signals;

utilizing a stratum clock state machine to control a multiplexer;

utilizing the multiplexer to switch an input of a main clock between each of the pair of

input clock signals;

inducing a phase build-out activity;

transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
providing the stratum clock state machine with a user selection input, wherein the user  
selection input includes at least one member selected from the group consisting of: a select  
freerun mode, a select reference A mode, a select reference B mode and a select holdover mode.

15. **(Cancelled)**

16. **(Currently Amended)** A method, comprising:

receiving a pair of input clock signals;

utilizing a stratum clock state machine to control a multiplexer;

utilizing the multiplexer to switch an input of a main clock between each of the pair of

input clock signals;

inducing a phase build-out activity;

transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
providing the stratum clock state machine with a frequency offset input including:

receiving a frequency offset signal produced by each of a pair of input digital  
phase-locked loops; and  
measuring the frequency offset signal.

17. **(Original)** The method of claim 16, further comprising setting the stratum clock state machine to the stratum clock state machine offset state if a measured frequency offset signal is greater than approximately 2.4 parts per million.

18. **(Original)** The method of claim 17, further comprising maintaining the stratum clock state machine offset state for approximately an additional 12 seconds after the measured frequency offset signal is de-asserted.

19. **(Currently Amended)** A method, comprising:  
receiving a pair of input clock signals;  
utilizing a stratum clock state machine to control a multiplexer;  
utilizing the multiplexer to switch an input of a main clock between each of the pair of  
input clock signals;  
inducing a phase build-out activity;  
transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
providing the stratum clock state machine with a frequency error input including:  
    receiving a frequency error signal produced by each of the pair of input digital  
    phase-locked loops; and  
    measuring the frequency error signal.

20. **(Original)** The method of claim 19, further comprising setting the stratum clock state machine to a stratum clock state machine holdover state if a measured frequency error signal is greater than approximately 14.4 parts per million.

21. **(Original)** The method of claim 20, further comprising applying an approximately twenty-five second frequency history to the frequency synthesizer in the main clock.

22. **(Currently Amended)** A method, comprising:

receiving a pair of input clock signals;  
utilizing a stratum clock state machine to control a multiplexer;  
utilizing the multiplexer to switch an input of a main clock between each of the pair of  
input clock signals;  
inducing a phase build-out activity;  
transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
providing the stratum clock state machine with a phase step input including:  
    receiving a phase step signal produced by each of the pair of input digital phase-  
    locked loops; and  
    measuring the phase step signal.

23. **(Original)** The method of claim 22, further comprising setting the stratum clock state machine to the stratum clock state machine holdover state if a measured phase step signal is greater than approximately 1.4 microseconds.

24. **(Original)** The method of claim 23, further comprising performing a phase buildout function for approximately 12 seconds.

25. **(Currently Amended)** A method, comprising:  
receiving a pair of input clock signals;  
utilizing a stratum clock state machine to control a multiplexer;  
utilizing the multiplexer to switch an input of a main clock between each of the pair of  
input clock signals;  
inducing a phase build-out activity;  
transmitting an output clock signal; and ~~The method of claim 1, further comprising~~  
providing a set of three timers, wherein each timer is set by a state machine input event, including: a phase buildout timer, a hold timer, and a skip timer.

26. **(Original)** The method of claim 25, further comprising clearing the set of three timers

when a reference switch is detected.

27. (Cancelled)

28. (Cancelled)

29. (Cancelled)

30. (Cancelled)

31. (Cancelled)

32. (Cancelled)

33. (Cancelled)

34. (Cancelled)

35. (Cancelled)

36. (Cancelled)

37. (Cancelled)

38. (Cancelled)

39. (Cancelled)

40. (Cancelled)

41. (Cancelled)

42. (Cancelled)

43. (Cancelled)

44. (Cancelled)

45. (Cancelled)

46. (Cancelled)

47. (Cancelled)

48. (Cancelled)